ANTISCIVOLO SYSTEM

DRACO

FLOORING
LINE

NON-SLIP TREATMENT FOR SURFACES AND FLOORS

COLOURLESS NON-SLIP COATING FOR CERAMIC TILE, CONCRETE AND STONE AGGREGATE MATERIALS

ANTISCIVOLO SYSTEM is a clear colourless coating that raises static and dynamic friction efficiency of common floor types by reducing slipping and accident risks in public places and/or the workplace. Wet flooring proves quite safe and meets current regulatory requirements (with prior testing and certification).

IDEAL FOR

- ✓ Anti-slip treatment of ceramic tiles, clinker, natural stone and cementitious materials.
- ✓ Ensuring safety compliance of flooring in work areas, schools and in public places such as hotels, restaurants, conference rooms, gymnasiums, cafeterias, laboratories, etc.
- ✓ Reducing the causes of slipping in a domestic environment by treating the areas most at risk (bathrooms, kitchens, utility rooms, etc.).
- ✓ Pools, playgrounds, locker and changing facilities
- ✓ Multiple other industries

SURFACES SUITABLE FOR APPLICATION

Ceramic, porcelain and clinker tile; marble; stone and stone aggregate materials; concrete and cement-based materials.

HOW IT WORKS

Applied to a clean and oil residue-free surface, **ANTISCIVOLO SYSTEM** interacts with the surface material's microstructure, creating a lattice profile (similar to a tire print), which remarkably increases friction efficiency when coming into contact with water and, as a result, the floor's safety.

AESTHETIC APPEARANCE OF THE TREATED SURFACE

ANTISCIVOLO SYSTEM is colourless and does not alter the appearance of the surface on which it is applied. Given the alkaline nature of **ANTISCIVOLO SYSTEM**, it is still advisable to test-apply it to a small area to double-check for any potential alteration in the floor surface's gloss or aesthetic appearance.

©Copyright 2012 -All rights reserved -The following specifications provide reliable details about our current best knowledge and know-how. Changes may take place according to the accuracy of the application steps we shall not be held responsible for. For this reason, our warranty only covers the quality and life of the products according to their specifications. This issue invalidates and replaces the previous ones.

DRACO Italiana SpA • via Monte Grappa, 11 D-E • 20067 Tribiano (MI) t. +39 02 90632917 • f. +39 02 90631976 • info@draco-edilizia.it

DRACO FLOORING LINE

HOW TO USE

Use gloves, mask and safety glasses.

1) The surface to be treated must be clean, dry, and free of oil and residual debris (use specific purpose cleaner Antiscivolo System Cleaner);

2) Apply **ANTISCIVOLO SYSTEM** to the area to be treated;

3) Spread the product and polish the surface using a felt applicator disc (polishing type machine);

4) Continue polishing for about 20-35 minutes, keeping the surface wet by adding additional **ANTISCIVOLO SYSTEM**;

6) Rinse the surface with water and dry it;

7) Verify the level of floor friction and, if not satisfactory, repeat the process.

CONSUMPTION

ANTISCIVOLO SYSTEM's approximate yield is about 9 m^2 of treated surface per litre of product. Some factors such as ventilation, support surface porosity and state of cleanliness may affect product yield.

COATING DURABILITY

With normal use, its durability is 5 years.

TECHNICAL SPECIFICATIONS

APPEARANCE	Liquid, transparent
ODOR	Acidic (slight)
SPECIFIC GRAVITY	1.04 kg/l +/-0.01
pH	4 to 4.5
BOILING/CONDENSATION POINT	100°C
MELTING/FREEZING POINT	0°C
VAPOR PRESSURE at 20°C	2.2 kPa (16.5 mmHg)
VAPOR DENSITY	0.62
VOLATILITY	<91%
EVAPORATION RATE	0.36
VOC	- 5 %
SOLUBILITY	Easily soluble in cold water, hot water, methanol, acetone
CONSUMPTION	about 9 m^2/l of product
PACKAGING	1 kg bottle - 5-10-20 kg Can

Legal notice - SLCMP version dated 01.03.2017

In the technical specifications herein, Draco Italiana s.p.a. used the indicators therein specified, with the relevant standards.

Please check if this Sheet and the figures therein contained apply to the product batch you are interested in or if they have been overridden by any later release. If in doubt, check whether this Sheet matches the one applicable at the time of finalising the sales agreement, at **www.draco-edilizia.it**, and/or contact our Engineering Department.

No advice provided by our staff, either verbally or in writing at your request, about the potential applications of the Products shall be binding under the sales agreement or shall be considered an integral part of the agreement. Such advice is based on our experience and on the best available practical and/or scientific knowledge; as such, it shall not be binding or conditional on the buyer or user. Please try our products first to find out whether they are fit for your intended use or application; in any case, you shall be solely responsible for your choice.

©Copyright 2012 -All rights reserved -The following specifications provide reliable details about our current best knowledge and know-how. Changes may take place according to the accuracy of the application steps we shall not be held responsible for. For this reason, our warranty only covers the quality and life of the products according to their specifications. This issue invalidates and replaces the previous ones.

DRACO Italiana SpA - Via Monte Grappa 11 D-E, I-20067 Tribiano, Milan, Italy - Tel. +39 0290632917 - Fax. +39 0290631976 - info@draco-edilizia.it