

DISARMIX W

WATER-EMULSIFIABLE FORM RELEASE
AGENT FOR WOODEN FORMWORK



DISARMIX W is an emulsifiable chemical form release agent based on special synthetic oils and high quality emulsifiers, which enables easy demoulding and protection of wooden formwork. Mixed with water, it guarantees perfect release of concrete for every type of casting.

ADVANTAGES

- ✓ Quick and easy application;
- ✓ reduced cleaning and maintenance time;
- ✓ protection of wooden or plywood formwork;
- ✓ does not alter the original colour of the structure.

FIELDS OF APPLICATION

DISARMIX W is particularly suitable for timber or plywood formwork and for all types of castings, always ensuring excellent results in terms of release and the "surface finish". It can be applied even at low temperatures and does not alter the original colour of the concrete.



INSTRUCTIONS FOR USE

DISARMIX W is mixed with water in the following proportions: 1 part **DISARMIX W** in 15 ± 20 parts water. It is advisable to remove foreign materials or fragments of hardened concrete from the formwork before applying the release agent.

PRECAUTIONS

Use according to the instructions on the safety and technical data sheet. Use full protective clothing.
See toxicological data sheet.

PACKAGING AND STORAGE

- 10-20 litre canisters
- 200 litre drums
- 1000 litre cistern

DISARMIX W retains its properties for 1 year when kept in its sealed packaging and stored at room temperature above 0°C away from heat sources and open flames.



YIELD

1 litre of **DISARMIX W**, to be diluted in water, per 80-100 m² of surface area.

SPECIFICATION ITEM

DISARMIX C is an emulsifiable chemical form release agent supplied by DRACO Italiana SpA that can be used on wooden or plywood formwork to obtain concretes with an excellent "surface finish" free of haloes or stains, and allows for quick and easy release of castings.

TECHNICAL SPECIFICATIONS

APPEARANCE	Liquid
COLOUR	Amber yellow
DENSITY	0.885 ± 0.015 kg/l
KINEMATIC VISCOSITY	12.72 cSt at 40°C
PERMISSIBLE APPLICATION TEMPERATURE	> 0°C
FLASH POINT	> 170°C
SOLUBILITY	Emulsifiable in water

Legal notes – SLCMP version of 01.03.2017

For the values and technical data in this Data Sheet, Draco Italiana s.p.a. adopts the parameters shown in the Data Sheet with the relative standards of reference.

The Customer is required to verify that this sheet and the values shown are valid for the product batch of interest and are not exceeded when replaced by subsequent editions. For any doubts, compare the technical data sheet with the one in force at the time the sales contract was completed on the website www.draco-edilizia.it, and/or contact the Technical Office.

No advice relating to the use of the Products provided by our personnel in verbal or written form at the Customer's request constitutes an ancillary obligation of the purchase contract, and cannot in any way represent a contractual service. It is based on our experience and limited to the current state of practical and/or scientific knowledge; it is therefore not binding for the customer or the applier. In particular, the Customer is required to test our products to check their suitability with respect to the type of application and intended use, and remains solely responsible for the choices made.