DRACOFILLER

MICROMETRIC FILLERS FOR ANTI-SLIP FINISHES

TO BE USED IN COMBINATION WITH POLIPLATE 2



DRACOFILLER is made up of micrometric spheroidal silica fillers, extremely wear-resistant, to be added to the two-component aliphatic polyurethane resin POLIPLATE 2 (DRACOFLOOR system) or to the DRACO seamless resin coatings to create an anti-slip finish.

DRACOFILLER should be added to the resin at a rate of 3-10% in weight, by adjusting the dosage according to the intensity of the anti-slip effect to be achieved.

IDEAL FOR

- √ Obtaining the anti-slip finish in the DRACOFLOOR systems.
- √ Obtaining an anti-slip effect when used in combination with DRACO seamless resin coatings.

HOW TO USE

Prepare the two-component aliphatic polyurethane resin POLIPLATE 2 as indicated in the technical data sheet and later add, under continuous stirring at a low speed, **DRACOFILLER** at a rate of 3-10% in weight, according to the intensity of the antislip effect to be achieved. After mixing with DRACOFILLER, apply POLIPLATE 2 evenly with short-haired roller.

For applications on small surfaces, **DRACOFILLER** can be applied by dry shake between the two coats of POLIPLATE 2 resin. After applying the first coat of POLIPLATE 2, distribute **DRACOFILLER** evenly on the layer of resin which is still fresh; wait for the first coat to dry completely and apply the second layer of resin.

FEATURES

APPEARANCE AND MATERIAL:

Silica microspheres

SIZE:

70 - 110 micron

CONSUMPTION:

 $5-20 \text{ g/m}^2$

PACKAGING:

1 kg pail

Legal notes - SLCMP version of 01.03.2017

As to the values and technical data contained in this Data Sheet, Draco Italiana s.p.a. adopts the parameters stated therein along with the relevant standards.

The Customer is required to verify that this Data Sheet as well as the values herein included are valid for the product batch at issue and that the same are not outdated due to later revisions. In doubt, the Customer may make sure that the Data Sheet conforms with the one in force at the time of completion of the sales contract being published on the website www.draco-edilizia.it, and/or confer with the Technical Office.

Any suggestions regarding the use of the Products provided by our personnel verbally or in writing at the Customer's request are not an ancillary obligation of the sales contract and can in no way represent a contractual service of ours. They are based on our experience and limited to the present state of practical and/or scientific knowledge; they are therefore not binding on the customer or the layer. In particular, the Customer is required to test our products to verify their suitability for the intended application and use, and remains solely responsible for the choices made.

