

RESICLEANER HD

NON-FOAMING DEGREASER FOR IN-DEPTH CLEANING OF RESIN FLOORS



RESICLEANER HD (HEAVY DUTIES) is a non-foaming detergent with high emulsifier content and strong degreasing activity for cleaning resin floors with stubborn dirt such as mineral and organic oils, food-grade grease, lubricating oils, etc. **RESICLEANER HD** is indicated for manually or mechanically cleaning all resin surfaces both in industrial and in commercial/domestic environment, where it can remove even the most stubborn stains and dirt residues, while respecting the polymeric matrix of the resin surface. **RESICLEANER HD** is easy to use, as it requires no rinsing, moreover it leaves no residues or halos of any kind.

BENEFITS

RESICLEANER HD is a multi-purpose detergent for resin floors having a high cleaning power and with the following features:

- ✓ **HIGH CLEANING POWER:** RESICLEANER HD cleans without being aggressive to the surfaces and effectively removes even the grease/oil residues and the most stubborn stains, thanks to its strong degreasing activity.
- ✓ **EASY TO APPLY:** RESICLEANER HD is easy to apply both manually and by mechanical means.
- ✓ **SPECIFIC FOR RESIN COATINGS:** RESICLEANER HD cleans the coatings made up of DRACO epoxy resin, polyurethane resin and resin-cement formulas, by respecting the superficial microstructure without modifying the colours or treatment duration.
- ✓ **WITHOUT RINSING AND WITH QUICK DRYING:** RESICLEANER HD requires no rinsing and dries quickly, thus permitting immediate use of the floor.
- ✓ **IT LEAVES NO RESIDUES OR HALOS:** RESICLEANER HD is easy to apply and leaves no stripes, stains or halos.
- ✓ **NON-TOXIC:** RESICLEANER HD is not hazardous to humans and to the environment.



AREAS OF APPLICATION

The high cleaning power with dirt disaggregating activity makes **RESICLEANER HD** particularly suitable to:

- ✓ **the in-depth cleaning of resin floors made with EPOPLATE, EPOLEVEL, and with the resin systems DRACOFLOOR and of resin-based floors at large.**
- ✓ cleaning floors of warehouses, food industries, hospitals, canteens.

PREPARATION

Dilute **RESICLEANER HD** with 5-20% of water according to the degree of grease and dirt present on the floor.

PRECAUTIONS

Use rubber gloves and avoid direct contact with eyes and skin. In case of accidental contact, carefully wash with plenty of running water and possibly soap the parts of the body which came in contact with the product and seek medical advice.

Product for professional use. Before use carefully read the material safety data sheet.

HOW TO USE

- **Clean the surface** to be treated and check that no loose parts or residues of dust have remained.
- **Manual application** - after having diluted the product, pour **RESICLEANER HD** into the mop container and proceed with cleaning, by exerting a continuous friction on the dirty surface, or – while treating small areas – pour the product on a cloth/sponge or directly on the surface and remove dirt.
- **Mechanical application** - pour a diluted solution of **RESICLEANER HD** into the tank and use the product with washer-drier, single-brush floor cleaner or injection-extraction machine.

COMPOSITION

It contains anionic surfactants and aliphatic alcohols.

RESICLEANER HD is an EPD (Environmental Product Declaration) product. The content of this formula is compliant with the criteria of biodegradability established by EC Regulation No. 648/2004 on detergents.

PACKAGING AND STORAGE

RESICLEANER HD is packaged in:

- 1 kg bottles
- 5 - 10 kg cans

If the product is stored properly in its original packaging, indoors in a dry location, it maintains its original features for one year. Avoid storing the product at temperatures above 40 °C.

FEATURES

| | |
|---------------------------|-------------|
| PHYSICAL STATUS | liquid |
| COLOUR | yellow |
| SCENT | typical |
| DILUTION WITH WATER | 0.5 ÷ 3% |
| pH VALUE OF A 1% SOLUTION | 10-11 ± 0.5 |
| pH TEL QUEL | 12-13 ± 0.5 |
| SPECIFIC GRAVITY | 1.05 ± 0.01 |
| BIODEGRADABILITY | > 90% |

Legal notice - SLCMP version dated 01.03.2017

In the technical specifications herein, Draco Italiana s.p.a. used the indicators therein specified, with the relevant standards.

Please check if this Sheet and the figures therein contained apply to the product batch you are interested in or if they have been overridden by any later release. If in doubt, check whether this Sheet matches the one applicable at the time of finalising the sales agreement, at www.draco-edilizia.it, and/or contact our Engineering Department.

No advice provided by our staff, either verbally or in writing at your request, about the potential applications of the Products shall be binding under the sales agreement or shall be considered an integral part of the agreement. Such advice is based on our experience and on the best available practical and/or scientific knowledge; as such, it shall not be binding or conditional on the buyer or user. Please try our products first to find out whether they are fit for your intended use or application; in any case, you shall be solely responsible for your choice.