

DRAP293 - SANOSAN LEGANTE**Safety Data Sheet**

According to Annex II to REACH - Regulation 2015/830

SECTION 1. Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Code: DRAP293
Product name: SANOSAN LEGANTE

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: Binder for plaster mortars

1.3. Details of the supplier of the safety data sheet

Name: DRACO ITALIANA S.p.A.
Full address: Via Monte Grappa, 11 D-E
District and Country: 20067 Tribiano (MI)
Italia
Tel. +39 02.90632917
Fax +39 02.90631976

e-mail address of the competent person responsible for the Safety Data Sheet

info@draco-edilizia.it

1.4. Emergency telephone number

For urgent inquiries refer to

Centro Antiveleni di Bergamo 800883300 (Azienda Ospedaliera Papa Giovanni XXII)
Centro Antiveleni di Firenze 0557947819 (Az. Osp. "Careggi" U.O. Tossicologia Medica)
Centro Antiveleni di Foggia 80018345 (Az. Osp. Univ. Foggia)
Centro Antiveleni di Milano 0266101029 (Osp. Niguarda Ca' Granda)
Centro Antiveleni di Napoli 0817472870 (Az. Osp. "A. Cardarelli")
Centro Antiveleni di Pavia 038224444 (CAV Centro Nazionale di Informazione Tossicologica)
Centro Antiveleni di Roma 063054343 (CAV Policlinico "A. Gemelli")
Centro Antiveleni di Roma 0649978000 (CAV Policlinico "Umberto I")
Centro Antiveleni di Roma 06 68593726 (CAV "Osp. Pediatrico Bambino Gesù" Dip. Emergenza e Accettazione DEA)

SECTION 2. Hazards identification**2.1. Classification of the substance or mixture**

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2015/830. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

| | | |
|--|------|--------------------------------------|
| Serious eye damage, category 1 | H318 | Causes serious eye damage. |
| Skin irritation, category 2 | H315 | Causes skin irritation. |
| Specific target organ toxicity - single exposure, category 3 | H335 | May cause respiratory irritation. |
| Skin sensitization, category 1B | H317 | May cause an allergic skin reaction. |

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



DRAP293 - SANOSAN LEGANTE**SECTION 2. Hazards identification ... / >>**

Signal words: Danger

Hazard statements:

H318 Causes serious eye damage.
H315 Causes skin irritation.
H335 May cause respiratory irritation.
H317 May cause an allergic skin reaction.

Precautionary statements:

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P280 Wear protective gloves / eye protection / face protection.
P310 Immediately call a POISON CENTER / doctor / . . .
P261 Avoid breathing dust / fume / gas / mist / vapours / spray.
P403+P233 Store in a well-ventilated place. Keep container tightly closed.
P264 Wash . . . thoroughly after handling.

Contains: Portland cement clinker

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

SECTION 3. Composition/information on ingredients**3.2. Mixtures**

Contains:

| Identification | x = Conc. % | Classification 1272/2008 (CLP) |
|--------------------------------|---|--|
| Portland cement clinker | | |
| CAS | 65997-15-1 50 \leq x < 100 | Eye Dam. 1 H318, Skin Irrit. 2 H315, STOT SE 3 H335, Skin Sens. 1B H317 |
| EC | 266-043-4 | |
| INDEX | | |
| Reg. no. | Esente all'art. 2.7 (b) e Allegato V.10 REACH | |

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures**4.1. Description of first aid measures**

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately.

INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

Portland cement clinker

General notes

Personal protective equipment is not necessary for rescuers, who must avoid the inhalation of cement dust and contact with damp cement or with preparations containing it (concrete, mortar, plaster, etc.). If this is not possible, they must adopt the personal protective equipment described in Section 8.

In case of eye contact

Do not rub your eyes to avoid possible corneal damage caused by rubbing.

If present, remove contact lenses. Incline the head in the direction of the affected eye, open the eyelids well and rinse with plenty of water for at least 20 minutes to remove all residues. If possible, use isotonic water (0.9% NaCl). If necessary, contact an occupational health specialist or ophthalmologist.

In case of skin contact

For dry cement, remove and rinse thoroughly with water. For wet / damp concrete, wash the skin with plenty of water and mild pH soap or a

DRAP293 - SANOSAN LEGANTE**SECTION 4. First aid measures ... / >>**

suitable mild detergent. Remove contaminated clothing, shoes and glasses and clean them completely before re-using them. Consult a doctor in all cases of irritation or burns.

In case of inhalation

Take the person outdoors. Dust in the throat and nostrils should clean itself spontaneously. Contact a doctor if irritation persists, or if it occurs later or if you have discomfort, cough or other symptoms persist.

If swallowed

Do not induce vomiting. If the person is conscious, wash your mouth with water and give plenty of water to drink. Consult a doctor immediately or contact a Poison Control Center.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

Portland cement clinker

Eyes: Eye contact with cement dust (dry or wet) can cause serious and potentially irreversible injury.

Skin: Cement and its preparations can have an irritating effect on damp skin (due to sweating or moisture) after prolonged contact or can cause contact dermatitis, after repeated contact.

Inhalation: repeated inhalation of cement dust or mixtures containing cement over a long period of time increases the risk of developing lung diseases.

Ingestion: in case of accidental ingestion, the cement can cause ulceration of the digestive system.

Environment: under normal conditions of use, cement is not dangerous for the environment.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

SECTION 5. Firefighting measures**5.1. Extinguishing media**

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

Portland cement clinker

Cement is not flammable.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Do not breathe combustion products.

Portland cement clinker

Cement is not combustible or explosive, it does not facilitate or fuel the combustion of other materials.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

Portland cement clinker

Cement does not present risks related to fire.

No special protective equipment is needed for firefighters.

DRAP293 - SANOSAN LEGANTE**SECTION 6. Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

If there are no contraindications, spray powder with water to prevent the formation of dust.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

Portland cement clinker

No specific emergency procedures are required.

In any case it is necessary to protect the eyes, skin and respiratory tract with personal protective equipment in situations with high levels of dustiness.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product and place it in containers for recovery or disposal. If there are no contraindications, use jets of water to eliminate product residues.

Make sure the leakage site is well aired. Evaluate the compatibility of the container to be used, by checking section 10. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

Portland cement clinker

Dry cement

Use dry cleaning methods such as vacuum cleaners or vacuum extractors (portable industrial units, equipped with high efficiency particulate filters or equivalent techniques), which do not disperse dust in the environment. Never use compressed air.

Ensure that workers wear appropriate personal protective equipment (see section 8) in order to avoid inhalation of dust and contact with skin and eyes and prevent the spreading of cement dust. Store spilled material in containers (eg silos, hoppers etc.) for future use.

Wet cement

Remove the wet cement and place it in a container. Allow the material to dry and solidify before disposing of it as described in Section 13

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage**7.1. Precautions for safe handling**

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

Portland cement clinker

Fire prevention measures

No precaution should be taken as the cement is neither combustible nor flammable.

Measures to prevent the generation of aerosols and dust

Do not sweep or use compressed air. Use dry cleaning methods (such as vacuum cleaners and vacuum extractors), which do not cause air leakage.

Environmental protection measures

During material handling, avoid dispersion in the environment.

In workplaces where the cement is being handled, stored and bagged, one must not drink, eat, or smoke.

In dusty environments, wear dust masks and protective glasses.

Use protective gloves to avoid skin contact.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

Portland cement clinker

DRAP293 - SANOSAN LEGANTE**SECTION 7. Handling and storage ... / >>**

White cement must be stored in waterproof, dry conditions (eg with minimal internal condensation), clean and protected from contamination. Risk of burial: the cement can thicken or stick to the walls of the confined space in which it is stored. Cement can collapse, collapse or fall unexpectedly.

To prevent burial or suffocation, do not enter confined spaces, such as silos, containers, bulk transport trucks, or other storage containers or containers that store or contain cement without adopting appropriate safety measures.

Do not use aluminum containers due to incompatibility of materials.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection**8.1. Control parameters**

Regulatory References:

TLV-ACGIH

ACGIH 2020

Portland cement clinker**Threshold Limit Value**

| Type | Country | TWA/8h | | STEL/15min | | Remarks / Observations | | |
|-----------|---------|--------|-----|------------|-----|------------------------|--|--|
| | | mg/m3 | ppm | mg/m3 | ppm | | | |
| TLV-ACGIH | | 1 | | | | RESP | | |

Health - Derived no-effect level - DNEL / DMEL

| Route of exposure | Effects on consumers | | | | Effects on workers | | | |
|-------------------|----------------------|----------|---------|----------|--------------------|----------|---------|----------|
| | Acute | Acute | Chronic | Chronic | Acute | Acute | Chronic | Chronic |
| Inhalation | local | systemic | local | systemic | local | systemic | local | systemic |
| | | | | | 1 | | | 1 |
| | | | | | mg/m3 | | | mg/m3 |

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

Portland cement clinker

The regulation (EC) n. 1907/2006 concerning the registration, evaluation, authorization and restriction of chemical substances (REACH), in Annex XVII, point 47, as amended by Regulation n. 552/2009, requires the prohibition to market and use cement and its preparations if they contain, once mixed with water, more than 0.0002% (2 ppm) of water-soluble chromium VI on the total dry weight of the cement itself.

Considering that the white cement, once mixed with water, does not contain more than 0.0002% (2 ppm) of water-soluble Cr (VI) on the total dry weight, the same mixture can be marketed without the addition of reducing agents.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

In the case of prolonged contact with the product, protect the hands with penetration-resistant work gloves (see standard EN 374).

Work glove material must be chosen according to the use process and the products that may form. Latex gloves may cause sensitivity reactions.

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

None required, unless indicated otherwise in the chemical risk assessment.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Portland cement clinker

Hand protection:

Use gloves with mechanical abrasion resistance according to EN ISO 388 with nitrile, neoprene or polyurethane coating, preferably 3/4 or

DRAP293 - SANOSAN LEGANTE

totally in the case of more severe activities. In the event of possible contact with a wet substance, use a glove with specific chemical protection according to EN ISO 374 with specific thickness and permeation degree (in particular alkali) depending on the type of use (immersion or possible accidental contact).

Respiratory protection:

When a person is potentially exposed to dust levels above the exposure limits, use appropriate respiratory protection commensurate with the level of dustiness and compliant with the relevant EN standards (eg facial filtering certified according to EN 149). Masks FFP2, FFP3.

SECTION 9. Physical and chemical properties**9.1. Information on basic physical and chemical properties**

| Properties | Value | Information |
|--|----------------------------|-------------|
| Appearance | powder | |
| Colour | grey | |
| Odour | odourless | |
| Odour threshold | Not available | |
| pH | Not available | |
| Melting point / freezing point | Not available | |
| Initial boiling point | Not applicable | |
| Boiling range | Not available | |
| Flash point | Not applicable | |
| Evaporation rate | Not applicable | |
| Flammability (solid, gas) | Not available | |
| Lower inflammability limit | Not available | |
| Upper inflammability limit | Not available | |
| Lower explosive limit | Not available | |
| Upper explosive limit | Not available | |
| Vapour pressure | Not available | |
| Vapour density | Not applicable | |
| Relative density | Not available | |
| Solubility | partially soluble in water | |
| Partition coefficient: n-octanol/water | Not applicable | |
| Auto-ignition temperature | Not available | |
| Decomposition temperature | Not available | |
| Viscosity | Not determined | |
| Explosive properties | Not available | |
| Oxidising properties | Not available | |

9.2. Other information

Information not available

SECTION 10. Stability and reactivity**10.1. Reactivity**

There are no particular risks of reaction with other substances in normal conditions of use.

Portland cement clinker

White cement, in the presence of water, for example in the production of concrete or mortar, or when it gets wet, produces a strongly alkaline substance.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

Portland cement clinker

As such, cement is stable the longer it is stored appropriately. It must be kept dry. Contact with incompatible materials should be avoided. Wet cement is alkaline and incompatible with acids, ammonium salts, aluminum and other non-noble metals. The cement in contact with the hydrofluoric acid decomposes producing corrosive silicon tetrafluoride gas. The cement reacts with water and forms silicates and calcium hydroxide. The silicates in the cement react with powerful oxidants such as fluorine, boron trifluoride, chlorine trifluoride, manganese trifluoride and oxygen bifluoride.

DRAP293 - SANOSAN LEGANTE**SECTION 10. Stability and reactivity ... / >>****10.3. Possibility of hazardous reactions**

No hazardous reactions are foreseeable in normal conditions of use and storage.

10.4. Conditions to avoid

None in particular. However the usual precautions used for chemical products should be respected.

Portland cement clinker

Moisture conditions during storage can cause lumps and loss of product quality.

10.5. Incompatible materials

Portland cement clinker

Wet white cement is alkaline and incompatible with acids, ammonium salts, aluminum and other non-noble metals. In contact with aluminum powders, wet white cement causes the formation of hydrogen.

10.6. Hazardous decomposition products

Information not available

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on toxicological effectsMetabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

ATE (Inhalation) of the mixture:

Not classified (no significant component)

ATE (Oral) of the mixture:

Not classified (no significant component)

ATE (Dermal) of the mixture:

Not classified (no significant component)

Portland cement clinker

LD50 (Dermal)

2000 mg/kg

SKIN CORROSION / IRRITATION

Causes skin irritation

Portland cement clinker

Cement in contact with damp skin can cause thickening, cracking and cracking of the skin. Prolonged contact in combination with existing abrasions can cause severe burns. Some individuals may develop eczema following exposure to wet cement dust, caused by the high pH that can induce irritating contact dermatitis after prolonged contact

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye damage

DRAP293 - SANOSAN LEGANTE**SECTION 11. Toxicological information ... / >>**

Portland cement clinker

The clinker caused a set of heterogeneous effects on the cornea and the calculated irritation index was 128.

Direct contact with cement can cause corneal injury due to mechanical stress, immediate or delayed irritation or inflammation. Direct contact with large amounts of dry cement or wet cement projections can cause effects ranging from moderate eye irritation (eg conjunctivitis or blepharitis) to chemical burns and blindness.

RESPIRATORY OR SKIN SENSITISATION

Sensitising for the skin

Skin sensitization

Portland cement clinker

Some individuals may develop eczema following exposure to wet cement dust, caused by an immunological reaction to soluble Cr (VI) that causes allergic contact dermatitis. The answer may appear in a variety of forms that can range from a mild rash to severe dermatitis. No sensitizing effect is expected if the cement contains a water-soluble reducing agent of Cr (VI) until the indicated period of effectiveness of this reducing agent is exceeded.

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

Portland cement clinker

No causal association was established between exposure to Portland cement and cancer.

Epidemiological literature does not support the identification of Portland cement as a suspected human carcinogen.

Portland cement is not classifiable as a human carcinogen (according to the ACGIH A4: agents that cause concern about the possibility of being carcinogenic to humans but that cannot be definitively evaluated due to the lack of data. In vitro studies or on animals do not provide indications of carcinogenicity that are sufficient to classify the agent with one of the other notations). Based on available data, it does not fall within the classification criteria.

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

May cause respiratory irritation

Portland cement clinker

Cement dust can irritate the throat and respiratory system. Coughing, sneezing and out of breath may occur following exposures above the occupational exposure limits.

Overall, the evidence gathered clearly indicates that occupational exposure to cement dust has produced deficits in respiratory function. However, the evidence currently available is insufficient to establish with certainty the dose-response relationship for these effects.

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

Portland cement clinker

There is an indication of COPD. The effects are acute and due to high exposures. No chronic effects or low concentration effects were observed. Based on available data, it does not fall within the classification criteria.

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

SECTION 12. Ecological information

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

12.1. Toxicity

Portland cement clinker

DRAP293 - SANOSAN LEGANTE**SECTION 12. Ecological information ... / >>**

Cement is not dangerous for the environment. Ecotoxicity tests with Portland cement on Daphnia magna and Selenastrum coli have shown a small toxicological impact. So the LC50 and EC50 values cannot be determined. There are no indications of toxicity in the sedimentary phase. The addition of large amounts of cement to water can, however, cause an increase in pH and can therefore be toxic to aquatic life in certain circumstances.

12.2. Persistence and degradability

Information not available

12.3. Bioaccumulative potential

Information not available

12.4. Mobility in soil

Information not available

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

12.6. Other adverse effects

Information not available

SECTION 13. Disposal considerations**13.1. Waste treatment methods**

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

Portland cement clinker

Product - unused residue or dry spill

CER: 10 13 06 (Powders and particulates)

Collect unused dry residues or dry spills as they are. Mark the containers. If necessary, re-use based on storage life considerations and the obligation to avoid exposure to dust. In case of disposal, harden with water and dispose of according to "Product - after addition of water, hardened".

Product - sludge

Allow to harden, avoid entry into sewage and drainage systems or into water bodies (for example water courses) and dispose of as described below in "Product - after addition of water, hardened".

Product - after adding water, hardened

Dispose of according to Legislative Decree 152/2006 and subsequent amendments. Avoid entry into the sewage system. Dispose of the hardened product as concrete waste. Due to inertization, solid waste is not dangerous.

CER: 10 13 14 (waste and cement sludge) or 17 01 01 (cement).

Packaging

Empty the packaging completely and manage it in accordance with Legislative Decree 152/2006 and subsequent amendments.

DRAP293 - SANOSAN LEGANTE**SECTION 14. Transport information**

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

14.1. UN number

Not applicable

14.2. UN proper shipping name

Not applicable

14.3. Transport hazard class(es)

Not applicable

14.4. Packing group

Not applicable

14.5. Environmental hazards

Not applicable

14.6. Special precautions for user

Not applicable

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Information not relevant

SECTION 15. Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Seveso Category - Directive 2012/18/EC: None

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Contained substance

| | | |
|---|----|-------------------|
| Point | 75 | Calcium Carbonate |
| Reg. no.: Esentato ai sensi dell'allegato V.7 | | |

Regulation (EC) No. 2019/1148 - on the marketing and use of explosives precursors

Not applicable

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage \geq than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

DRAP293 - SANOSAN LEGANTE**SECTION 15. Regulatory information ... / >>**

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

| | |
|----------------------|--|
| Eye Dam. 1 | Serious eye damage, category 1 |
| Skin Irrit. 2 | Skin irritation, category 2 |
| STOT SE 3 | Specific target organ toxicity - single exposure, category 3 |
| Skin Sens. 1B | Skin sensitization, category 1B |
| H318 | Causes serious eye damage. |
| H315 | Causes skin irritation. |
| H335 | May cause respiratory irritation. |
| H317 | May cause an allergic skin reaction. |

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
4. Regulation (EU) 2015/830 of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament

DRAP293 - SANOSAN LEGANTE

12. Regulation (EU) 2016/1179 (IX Atp. CLP) 13. Regulation (EU) 2017/776 (X Atp. CLP)
14. Regulation (EU) 2018/669 (XI Atp. CLP)
15. Regulation (EU) 2018/1480 (XIII Atp. CLP)
16. Regulation (EU) 2019/521 (XII Atp. CLP)
17. Regulation (EU) 2019/1148
18. Regulation (EU) 2020/217 (XIV Atp. CLP)

- The Merck Index. - 10th Edition
- Handling Chemical Safety
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.